

Commercial Meter Pedestals

CP3A 12"-Wide Slim Line



- Type 3R construction
- Ring or ringless meter sockets with bypass
- Ratings available through 100 Amps / meter
- Ratings available up to 480 Volts—1Ø3W
- UL Listed
- Compatible with a variety of circuit breakers
- Opened meter cover exposes the entire meter with no walls obscuring access
- Up to 12 circuits available
- Side entrance for utility section
- Customer section cover is hinged
- Hinged deadfront provided
- Approximate weight: 171 lbs. steel
- Anchor bolt catalog number for (4): CP-ABK5/8
- Optional embedded cement pad base: CP-12-PAD
- Meets most utility requirements (consult local utility)

Milbank commercial pedestals provide a low-cost, effective alternative to the post-and-strut method of providing site power. Avoid the hassle and extra labor involved with strut farms by using Milbank pedestals. Inspector-friendly Milbank pedestals are UL-listed as a system and allow for a quick install in just 1 man-hour vs. 16 (or more) man-hours with a traditional strut/component installation.

These units have a single cabinet with all the required utility terminations, meter sockets with test / bypass provisions, main breakers and customer sections. They are factory wired and UL Listed.

Suggested Uses

- Traffic Signal Equipment and Metering
- Street Lighting and Metering
- Control and Metering
- Irrigation
- Pump Station Control and Metering
- Signal Light Control and Metering
- Remote Electrical Distribution

Toll Free: 877.483.5314

Phone: 816.483.5314

Fax: 816.483.6357

www.milbankmfg.com

CMP12SLIM 6/10 (3K)



MILBANK[®]

Commercial Meter Pedestals

CP3A 12"-Wide Slim Line

