

HEAVY DUTY LEVER BYPASS METERING – MINNEAPOLIS STOCK

200 Amp Std.– 5 Terminal

U4801-O-5T9UGHDLB
U4801-XL-5T9OH/UGHDLB
U4550-RL-5T9OHHDLB
U9865-RRL-5T9OH/UG (Studs)HDLB
U4724-O-5T9*PED (not free standing)HDLB

*free standing w/ S3488 Ext. Kit



← U4801-XL-5T9

200 Amp Std.– 5 Terminal Gang

U2872-XT-5T9OH/UGHORIZ.2 GANGHDLB
U2873-XT-5T9OH/UGHORIZ.3 GANGHDLB
U2874-XT-5T9OH/UGHORIZ.4 GANGHDLB
U2875-XT-5T9OH/UGHORIZ.5 GANGHDLB
U2876-XT-5T9OH/UGHORIZ.6 GANGHDLB
U4768-O-5T9UGVERT. PED.2 GANGHDLB



U2873-XT-5T9

200 Amp Std.– 5 Terminal w/Breakers Installed

U3791N-RXL-100-5T9OH/UGHDLB
U3791N-RXL-150-5T9OH/UGHDLB
U3791N-RXL-200-5T9OH/UGHDLB
U3995-XL-200-5T9OH/UG w/4 extra brkr. spacesHDLB
U4834-XL-200-5T9OH/UG w/generator provisionHDLB
U5712-XL-200-5T9*OH/UG w/6-12 avail.circuitsHDLB

*Use with K5060 Deadfront/Transfer Bar Kit to accommodate hook up of a back-fed reserve generator

U5712-XL-200-5T9 →



200 Amp Std.– 7 Terminal

U4701-XLOH/UGHDLB
U9761-RRLOH/UG (studs)HDLB

320 Amp Std.– 5 Terminal

U1079-R-5T9OH (studs)HDLB
U1129-O-5T9UG (studs)HDLB
U2448-X-5T9OH/UG (studs)HDLB
U4031-O-2/200-5T9OH/UG w/breakers installedHDLB
U5059-X-2/200-5T9OH/UG w/breakers installedHDLB



← U1079-X-5T9

200 Amp Std.– 5 Terminal–Breaker Provision–Gang**

U4372-XT-5T9OH/UG2 GANGHDLB**
U4373-XT-5T9OH/UG3 GANGHDLB**
U4374-XT-5T9OH/UG4 GANGHDLB**
U4375-XT-5T9OH/UG5 GANGHDLB**
U4376-XT-5T9OH/UG6 GANGHDLB**

**Use TQDL - GE or BJ - Cut.-Ham. 150-200A Breaker, 100-125A universal plug-in

200 Amp Pedestal– 5 Terminal–Breaker Provision

U4322-O-5T9SINGLEHDLB**
U4323-O-5T9DOUBLEHDLB**
U4833-O-5T9WALL MOUNTHDLB***

**Use same breaker as above

***Use Milbank UQFP or UQFPH series breaker

320 Amp Std.– 7 Terminal

U2120-XUGHDLB
U2594-XOH/UGHDLB

LEGEND

- O.....Blank Top
- XL.....Small Closure Plate on Top
- X.....Large Closure Plate on Top
- RRL.....Hub Opening with Small Adapter
- RXL.....Large Opening with Adapter & Closure Plate
- XT.....Twin Large Opening with Closure Plate
- OH.....Overhead
- UG.....Underground
- 5T9.....5th Terminal at 9 o'clock
- HDLB.....Heavy Duty Lever Bypass

Lee-Noonan Company

2230 County Road H2, Moundsview MN 55112
Ph. 763-560-1228 • Fx. 763-560-3282

MILBANK
www.milbankmfg.com

MILBANK® METER SOCKET ACCESSORIES

INTERCHANGEABLE UNIT HUBS



HUB ADAPTER PLATE

DESCRIPTION	SUFFIX	CAT. #
HUB ADAPTER	-RRL	S8324

(Converts 4" opening to 2½" opening.)



SMALL "RL" OPENING

SUFFIX	SIZE	MILBANK NO.
WL	1"	A7514
YL	1¼"	A7515
ZL	1½"	A7516
DL	2"	A7517
EL	2½"	A7518



REMOVABLE HUB CLOSING PLATE

DESCRIPTION	SUFFIX	CAT. #
SMALL (for -RL opening)	-XL	A7551
LARGE (for -R opening)	-X	A9064

TOP SUFFIX CHART

SUFFIX	TOP DESCRIPTIONS
O	Plain Top
RL	Small Hub Opening
R	Large Hub Opening
XL	Small Closing Plate
X	Large Closing Plate
RXL	Large Opening adapted to small C.P.
RRL	Large Opening adapted to small H.O.
XT	Twin Large Hub Openings with C.P.s

HUB SUFFIX CHART

SUFFIX	HUB SIZE	APPLICATION
WL	1"	For -RL Opening
YL	1¼"	For -RL Opening
ZL	1½"	For -RL Opening
DL	2"	For -RL Opening
EL	2½"	For -RL Opening
F	3"	For -R Opening
G	3½"	For -R Opening
H	4"	For -R Opening

METER CLOSING PLATE



6003
(Gray Plastic — Ring-type & Ringless)

BYPASS LINK




K8180
(Bypass links sold in pairs)

*HEAVY DUTY FIFTH TERMINAL



K3865
(K3866 without neutral wire)
*Both kits for units manufactured after August, 1992



DEADFRONT/TRANSFER BAR KIT


K5060

ISOLATED NEUTRAL KIT



K1047

ANTI-INVERSION CLIP



K4802

CONNECTOR KITS



SINGLE

For use with 3/8"-16 stud type units only



TWIN


SUFFIX	CATALOG #	(3 per set) – 1 Ø
K1	K1539	6-350 kcmil
K3	K1540	4-600 kcmil or (2) 1/0-250 kcmil
K3L	K1540L	4-600 kcmil or (2) 1/0-250 kcmil Non-rotating

SUFFIX	CATALOG #	(4 per set) – 3 Ø
K5	K3082	6-350 kcmil
K7	K3441	4-600 kcmil or (2) 1/0-250 kcmil

SUFFIX	CATALOG #	(3 per set) – 1 Ø
K2	K1350	6-350 kcmil
K2L	K1350L	6-350 kcmil Non-rotating
K4	K1541	4-600 kcmil

SUFFIX	CATALOG #	(4 per set) – 3 Ø
K6	K3442	6-350 kcmil
K8	K3083	4-600 kcmil

LOAD TAP CONNECTORS (3 per set)



Replaces the **load side** slide-in nut assembly on Milbank 200 amp sockets. Allows for a 100 amp tap location in addition to the #6-350 kcmil load-side connector. **K5022** Includes Safety Barrier Extensions—for applications over 300 VAC.

K4977-INT INTERNAL HEX
K5022-INT INTERNAL HEX