

# 60 Amp Non-Fusible AC Disconnect

## U3802



- UL/cUL listed as Enclosed Pullout Switch UL 1429
- Type 3R rainproof enclosure
- Duplex ground connector
- Six 1" concentric knockouts
- 1Ø, 240 VAC
- Standard package of 6
- Pad-lockable door
- Removable front cover and deadfront



Milbank's air conditioner / equipment disconnects have a compact design. To ensure the safest conditions, we designed our disconnect pullouts to be reversible so they may be reinstalled in the OFF position.

All units are designed with a padlock provision on the cover for security. This enclosure is constructed of G90 galvanized steel and finished with an attractive, light gray, baked powder coating. Our state of the art finish combines epoxy and polyester hybrid resins into a hybrid powder coating which is then electrostatically applied. This offers a durable, non-fading finish.

AMP	TYPE	CATALOG NUMBER	MAX H.P.	WT. @ #	LINE & LOAD CONNECTOR WIRE RANGE		GROUND CONNECTOR WIRE RANGE CU/AL	DIMENSIONS			WIRE RATING	
					CU	AL		D"	W"	H"	1	2
60	NONFUSIBLE	U3802	10	3.25	#14-#2 AWG	#12-#2 AWG	#14-#2 AWG	2	5	7	60°/75°	60°/75°

Toll Free: 877.483.5314

Phone: 816.483.5314

Fax: 816.483.6357

www.milbankmfg.com

3802 5/10 (1K)